

Subminiature Fuse, 8.5 mm, Time-Lag T, 250 VAC, cULus



UL 248-14 · 250 VAC · Time-Lag T

See below:
[Approvals and Compliances](#)

Description

- Directly solderable on printed circuit boards
- Low Breaking Capacity


References

- [Packaging Details](#)
- Corresponding Fuseholder [FMS \(250V\)](#)

Weblinks

- [pdf datasheet](#), [html-datasheet](#), [General Product Information](#), [Packaging details](#), [Distributor-Stock-Check](#), [Detailed request for product](#)

Technical Data

| | |
|------------------------------|---|
| Rated Voltage | 250 VAC |
| Rated current | 0.063 - 10 A |
| Breaking Capacity | 50 A |
| Characteristic | Time-Lag T |
| Mounting | PCB, THT |
| Admissible Ambient Air Temp. | -40 °C to 85 °C |
| Climatic Category | 40/085/21 acc. to IEC 60068-1 |
| Material: Housing | Thermoplastic, UL 94V-0 |
| Material: Terminals | Tin-Plated Copper |
| Unit Weight | 0.53 g |
| Storage Conditions | 0 °C to 40 °C, max. 70% r.h. |
| Product Marking |  Type, Rated current, Rated Voltage, Characteristic, Certification marks |

| | |
|------------------------------|--|
| Soldering Methods | Wave Soldering Profile |
| Solderability | 235 °C / 2 sec acc. to IEC 60068-2-20, Test Ta |
| Resistance to Soldering Heat | 260 °C / 10 sec acc. to IEC 60068-2-20, Test Tb |
| Current Carrying Capacity | acc. to EIA/IS-722, Test 4.3.3 |
| Moisture Resistance Test | MIL-STD-202, Method 106E (50 cycles in a temp./mister chamber) |
| Terminal Strength | MIL-STD-202, Method 211A (Deflection of board 1 mm for 1 minute) |
| Case Resistance | acc. to EIA/IS-722, Test 4.7 >100 MΩ (between leads and body) |
| Mechanical Shock | (acc. to EIA/IS-722, Test 4.9) |
| Vibration, High Frequency | MIL-STD-202, Method 204D Shock 20 gn, 20 min, 10-2 kHz, 12 cyc. |
| Resistance to Solvents | MIL-STD-202, Method 215A |
| Flammability | UL 94V-0 (acc. to EIA/IS-722, Test 4.12) |


Approvals and Compliances

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in [Details about Approvals](#)

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 134485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.



Approvals

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: MSTU 250

| Approval Logo | Certificates | Certification Body | Description |
|---|--------------|--------------------|------------------------|
|  | UL Approvals | UL | UL File Number: E41599 |

Product standards

Product standards that are referenced

| Organization | Design | Standard | Description |
|--|-----------------------|--------------------|---|
|  | Designed according to | UL 248-14 | Low voltage fuses - Part 14: Additional fuses |
|  | Designed according to | CSA22.2 No. 248.14 | Low-Voltage Fuses - Part 14: Supplemental Fuses |





Application standards

Application standards where the product can be used

| Organization | Design | Standard | Description |
|--|--------------------------------|--------------|---|
|  | Designed for applications acc. | IEC/UL 60950 | IEC 60950-1 includes the basic requirements for the safety of information technology equipment. |


Compliances

The product complies with following Guide Lines

| Identification | Details | Initiator | Description |
|--|------------------------------|-------------|---|
|  | CE declaration of conformity | SCHURTER AG | The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008. |
|  | RoHS | SCHURTER AG | EU Directive RoHS 2011/65/EU |
|  | China RoHS | SCHURTER AG | The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS. |
|  | REACH | SCHURTER AG | On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force. |

Dimension [mm]

8.5 mm




Drilling diagram

Pre-Arcing Time

Rated Current I_n 1.0 x I_n min. 2.0 x I_n max.


| | | |
|----------------|-----|-------|
| 0.063 A - 10 A | 4 h | 120 s |
|----------------|-----|-------|

Time-Current-Curves



All Variants

| Rated Current [A] | Rated Voltage [VAC] | Breaking Capacity | Voltage Drop 1.0 In typ. [mV] | Power Dissipation 1.0 In typ. [mW] | Melting I ² t 10.0 In typ. [A ² s] | $c(U)_{US}$ | S | L | T | Order Number |
|-------------------|---------------------|-------------------|-------------------------------|------------------------------------|--|-------------|---|---|---|--------------|
| 0.063 | 250 | 1) | 544 | 37 | 0.0176 | ● | ● | | | 0034.7103 |
| 0.08 | 250 | 1) | 413 | 38 | 0.0313 | ● | ● | | | 0034.7104 |
| 0.1 | 250 | 1) | 318 | 35 | 0.0456 | ● | ● | | | 0034.7105 |
| 0.125 | 250 | 1) | 289 | 40 | 0.0567 | ● | ● | | | 0034.7106 |
| 0.16 | 250 | 1) | 219 | 38 | 0.0692 | ● | ● | | | 0034.7107 |
| 0.2 | 250 | 1) | 262 | 60 | 0.133 | ● | ● | | | 0034.7108 |
| 0.25 | 250 | 1) | 202 | 55 | 0.258 | ● | ● | | | 0034.7109 |
| 0.315 | 250 | 1) | 168 | 49 | 0.361 | ● | ● | | | 0034.7110 |
| 0.4 | 250 | 1) | 159 | 69 | 0.528 | ● | ● | | | 0034.7111 |
| 0.5 | 250 | 1) | 143 | 78 | 0.898 | ● | ● | | | 0034.7112 |
| 0.63 | 250 | 1) | 124 | 85 | 2.24 | ● | ● | | | 0034.7113 |
| 0.8 | 250 | 1) | 114 | 98 | 4.05 | ● | ● | | | 0034.7114 |
| 1 | 250 | 1) | 100 | 107 | 6.85 | ● | ● | | | 0034.7115 |
| 1.25 | 250 | 1) | 94 | 127 | 7.93 | ● | ● | | | 0034.7116 |
| 1.6 | 250 | 1) | 85 | 145 | 17.5 | ● | ● | | | 0034.7117 |
| 2 | 250 | 1) | 80 | 175 | 28.6 | ● | ● | | | 0034.7118 |
| 2.5 | 250 | 1) | 75 | 205 | 40.9 | ● | ● | | | 0034.7119 |
| 3.15 | 250 | 1) | 71 | 240 | 55 | ● | ● | | | 0034.7120 |
| 4 | 250 | 1) | 72 | 303 | 67.2 | ● | ● | | | 0034.7121 |
| 5 | 250 | 1) | 70 | 376 | 142 | ● | ● | | | 0034.7122 |
| 6.3 | 250 | 1) | 68 | 488 | 287 | ● | ● | | | 0034.7123 |
| 8 | 250 | 1) | 50 | 445 | 422 | ● | ● | | | 0034.7124 |
| 10 | 250 | 1) | 50 | 630 | 564 | ● | ● | | | 0034.7125 |
| 0.063 | 250 | 1) | 544 | 37 | 0.0176 | ● | | ● | | 0034.7203 |
| 0.08 | 250 | 1) | 413 | 38 | 0.0313 | ● | | ● | | 0034.7204 |
| 0.1 | 250 | 1) | 318 | 35 | 0.0456 | ● | | ● | | 0034.7205 |
| 0.125 | 250 | 1) | 289 | 40 | 0.0567 | ● | | ● | | 0034.7206 |

| Rated Current [A] | Rated Voltage [VAC] | Breaking Capacity | Voltage Drop 1.0 In typ. [mV] | Power Dissipation 1.0 In typ. [mW] | Melting I ² t 10.0 In typ. [A ² s] |  | S | L | T | Order Number |
|-------------------|---------------------|-------------------|-------------------------------|------------------------------------|--|---|---|---|---|--------------|
| 0.16 | 250 | 1) | 219 | 38 | 0.0692 | ● | ● | | | 0034.7207 |
| 0.2 | 250 | 1) | 262 | 60 | 0.133 | ● | ● | | | 0034.7208 |
| 0.25 | 250 | 1) | 202 | 55 | 0.258 | ● | ● | | | 0034.7209 |
| 0.315 | 250 | 1) | 168 | 49 | 0.361 | ● | ● | | | 0034.7210 |
| 0.4 | 250 | 1) | 159 | 69 | 0.528 | ● | ● | | | 0034.7211 |
| 0.5 | 250 | 1) | 143 | 78 | 0.898 | ● | ● | | | 0034.7212 |
| 0.63 | 250 | 1) | 124 | 85 | 2.24 | ● | ● | | | 0034.7213 |
| 0.8 | 250 | 1) | 114 | 98 | 4.05 | ● | ● | | | 0034.7214 |
| 1 | 250 | 1) | 100 | 107 | 6.85 | ● | ● | | | 0034.7215 |
| 1.25 | 250 | 1) | 94 | 127 | 7.93 | ● | ● | | | 0034.7216 |
| 1.6 | 250 | 1) | 85 | 145 | 17.5 | ● | ● | | | 0034.7217 |
| 2 | 250 | 1) | 80 | 175 | 28.6 | ● | ● | | | 0034.7218 |
| 2.5 | 250 | 1) | 75 | 205 | 40.9 | ● | ● | | | 0034.7219 |
| 3.15 | 250 | 1) | 71 | 240 | 55 | ● | ● | | | 0034.7220 |
| 4 | 250 | 1) | 72 | 303 | 67.2 | ● | ● | | | 0034.7221 |
| 5 | 250 | 1) | 70 | 376 | 142 | ● | ● | | | 0034.7222 |
| 6.3 | 250 | 1) | 68 | 488 | 287 | ● | ● | | | 0034.7223 |
| 8 | 250 | 1) | 50 | 445 | 422 | ● | ● | | | 0034.7224 |
| 10 | 250 | 1) | 50 | 630 | 564 | ● | ● | | | 0034.7225 |
| 0.063 | 250 | 1) | 544 | 37 | 0.0176 | ● | | ● | | 0034.7303 |
| 0.08 | 250 | 1) | 413 | 38 | 0.0313 | ● | | ● | | 0034.7304 |
| 0.1 | 250 | 1) | 318 | 35 | 0.0456 | ● | | ● | | 0034.7305 |
| 0.125 | 250 | 1) | 289 | 40 | 0.0567 | ● | | ● | | 0034.7306 |
| 0.16 | 250 | 1) | 219 | 38 | 0.0692 | ● | | ● | | 0034.7307 |
| 0.2 | 250 | 1) | 262 | 60 | 0.133 | ● | | ● | | 0034.7308 |
| 0.25 | 250 | 1) | 202 | 55 | 0.258 | ● | | ● | | 0034.7309 |
| 0.315 | 250 | 1) | 168 | 49 | 0.361 | ● | | ● | | 0034.7310 |
| 0.4 | 250 | 1) | 159 | 69 | 0.528 | ● | | ● | | 0034.7311 |
| 0.5 | 250 | 1) | 143 | 78 | 0.898 | ● | | ● | | 0034.7312 |
| 0.63 | 250 | 1) | 124 | 85 | 2.24 | ● | | ● | | 0034.7313 |
| 0.8 | 250 | 1) | 114 | 98 | 4.05 | ● | | ● | | 0034.7314 |
| 1 | 250 | 1) | 100 | 107 | 6.85 | ● | | ● | | 0034.7315 |
| 1.25 | 250 | 1) | 94 | 127 | 7.93 | ● | | ● | | 0034.7316 |
| 1.6 | 250 | 1) | 85 | 145 | 17.5 | ● | | ● | | 0034.7317 |
| 2 | 250 | 1) | 80 | 175 | 28.6 | ● | | ● | | 0034.7318 |
| 2.5 | 250 | 1) | 75 | 205 | 40.9 | ● | | ● | | 0034.7319 |
| 3.15 | 250 | 1) | 71 | 240 | 55 | ● | | ● | | 0034.7320 |
| 4 | 250 | 1) | 72 | 303 | 67.2 | ● | | ● | | 0034.7321 |
| 5 | 250 | 1) | 70 | 376 | 142 | ● | | ● | | 0034.7322 |
| 6.3 | 250 | 1) | 68 | 488 | 287 | ● | | ● | | 0034.7323 |
| 8 | 250 | 1) | 50 | 445 | 422 | ● | | ● | | 0034.7324 |
| 10 | 250 | 1) | 50 | 630 | 564 | ● | | ● | | 0034.7325 |

Availability for all products can be searched real-time: <https://www.schurter.com/en/Stock-Check/Stock-Check-SCHURTER>

1) 50 A @ 250 VAC

| Packaging Unit | S = | Plastic Bag (100 pcs.) |
|----------------|-----|-----------------------------|
| | L = | Bulk (100 pcs.) |
| | T = | Taped 36 cm Reel (750 pcs.) |